

# LED ceiling light



## Features



- Outdoor Advertising LED backlight instead of the fluorescent light box
- Super slim, Saving freight
- Integrated LED design IP65
- Convenient Installation
- Direct replacement of the same size as the ceiling lighting
- Build in Driver

## Applications

- Balcony, corridor, courtyard, parking lot, bathroom, kitchens, stairwells, Indoor signs backlight, such as cabinet light, shopping malls, hotel restaurant advertising signs architectural lighting

## Technical Specifications

Part No.	Wattage (W)	Voltage	Luminous (lm)	PF	CRI (Ra)	Dimensions (mm)	CCT (K)	Beam angle	IP	Working Temperature(°C)
DS-CL-08	8	220-240V	640	0.5	>80	198*99*39	2700-6000K	120°	IP65	-20°~40°
DS-CL-012	12	220-240V	900	0.5	>80	198*99*39	2700-6000K	120°	IP65	-20°~40°
DS-CL-015	15	220-240V	1200	0.5	>80	229*104*41	2700-6000K	120°	IP65	-20°~40°
DS-CL-018	18	220-240V	1400	0.5	>80	229*104*41	2700-6000K	120°	IP65	-20°~40°



✳ It can be available for wide voltage

[www.edisunlighting.com](http://www.edisunlighting.com)

